

CHRYSO®Delta 15S

Set retarding water reducing/ plasticizing admixture



CHRYSO
CONCRETE
SOLUTIONS

18/01/2024

DESCRIPTION

CHRYSO®Delta 15S slows down the hydration of cement by momentarily blocking the surface of the cement particles. At the end of setting, the concrete hardens rapidly and higher compressive strength is obtained after 28 days.

CHRYSO®Delta 15S has no surface tension effects. Its use in concrete modifies in no way the consistency of concrete.

CHRYSO®Delta 15S can be used simultaneously with high range water reducing superplasticizers.

BENEFITS

- **CHRYSO®Delta 15S** is used to adjust the workability retention and initial workability being fine-tuned thanks to the ultra / high range water reducing admixture.
- **CHRYSO®Delta 15S** can therefore be used for a wide range of concretes.
- **CHRYSO®Delta 15S** is the perfect solution in case of remote jobsite or heavy traffic, as well as temperature changes.
- **CHRYSO®Delta 15S** makes it possible to avoid re-tempering at the delivery point.
- **CHRYSO®Delta 15S** is particularly suited for cements for which workability retention is difficult to get and/or at high temperature.

FIELDS OF APPLICATION

- All cement types
- Ready-mix concrete
- Workability retention

CHARACTERISTICS

Product Nature	liquid
Color	Light brown
Lifetime	12 months
Specific gravity	1.080 ± 0.020
pH	6.00 ± 2.00

METHOD OF USE

- This product is completely miscible in water.
- This product must be added to the mixing water before adding to the mixer.
- The optimum dosage of this product can only be established after trial tests, taking into account the rheological characteristics and the required mechanical performances of the concrete.
- The optimum dosage of **CHRYSO®Delta 15S** can only be established after trial tests, taking into account local conditions, materials and specification requirements.
- **CHRYSO®Delta 15S** can be added at the concrete plant or on the job site. In case of addition in a mixing truck, it is recommended that the concrete be mixed at high speed for 1 minute per cubic yard of concrete (with a minimum of 6 min.)
- Because local job conditions vary, please contact your local **CHRYSO** sales representative for further assistance if using outside recommended dosage ranges.

Dosage :

0.5 to 2 litres for 100 kg of cement.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.ph

CHRYSO PHILIPPINES INC. 17 Main Ave. Severina Industrial Estate, ACSIE Comp. Km 16, West Service Rd. 1700 Paranaque City. Tél.:(+632) 823-1568 Fax:(+632) 823-6492

CHRYSO®Delta 15S

Set retarding water reducing/ plasticizing admixture



CHRYSO
CONCRETE
SOLUTIONS

18/01/2024

NORMATIVE AND REGULATORY INFORMATION

- This product conforms to ASTM C 494 Type B and D, and BSEN 934-2.

TEST SITE

PACKAGING

- 1000 L IBC
- 200 L drum
- 20 L bucket

PRECAUTIONS

- Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.
- Avoid prolonged exposure to high temperatures.
- Protect from frost.

SAFETY

CHRYSO®Delta 15S is not considered dangerous to handle. Please refer to the material safety data sheet for additional information.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.ph

CHRYSO PHILIPPINES INC. 17 Main Ave. Severina Industrial Estate, ACSIE Comp. Km 16, West Service Rd. 1700 Paranaque City. Tél.:(+632) 823-1568 Fax:(+632) 823-6492