

1164
8EN 934-2+A1:2012
1164-CPR-ADJ001

CHRYSO® Fluid Optima 185

1. dop point 1
EN 934-2+A1:2012 : T3.1/3.2

2. dop point 2
3. dop point 3
High range water reducing Super plasticizing admixture
4. dop point 4
CHRYSO SAS 7 rue de l'Europe - 45300 SERMAISES DU
LOIRET France

5. dop point 5
Système 2+
6. dop point 6
EN 934-
2+A1:2012
dop point 6
content
N° 1164-CPR-ADJ001

7. dop point 7

dop table header 1	dop table header 2	dop table header 3
Chloride Ions	≤ 0,100 %	EN 934-2+A1:2012
Equivalent Content NA_2O	≤ 0,50 %	EN 934-2+A1:2012
Corrosion	Contains only components from EN 934-1:2008, Annex A.1.	EN 934-2+A1:2012
Compressive strength (at equal w/c ratio)	at 28 days : Test mix ≥ 90% of control mix	EN 934-2+A1:2012
Air Content in Fresh Concrete (at equal w/c ratio)	Test mix ≤ 2% by volume above control mix	EN 934-2+A1:2012
Water Reduction	Test mix ≥ 12% compared with control mix	EN 934-2+A1:2012
Compressive strength (at equal consistence)	at 1 day : Test mix ≥ 140% of control mix at 28 days : Test mix ≥ 115% of control mix	EN 934-2+A1:2012
Air Content in Fresh Concrete (at equal consistence)	Test mix ≤ 2% by volume above control mix	EN 934-2+A1:2012
Increase in consistence	Increase in flow ≥ 160 mm from initial (350 ± 20) mm	EN 934-2+A1:2012
Retention of consistence	at 30 min : consistence test mix ≥ initial consistence of control mix	EN 934-2+A1:2012
Dangerous substances	See MSDS	EN 934-2+A1:2012

8. dop point 8

dop signature intro
Quentin BRANGER, Industrialisation & Products Quality Manager