

CHRYSO®Omega 85S

High Range Water Reducing Admix

DESCRIPTIF

CHRYSO®Omega 85S is a new generation water reducing admixture based on patented CHRYSO® polymer technology.

Thanks to its specifically designed molecular structure, CHRYSO®Omega 85S enables the concrete manufacturer to produce cohesive, low viscous concrete with long workability retention.

CHRYSO®Omega 85S has been developed to maintain fresh concrete workability without compromising the setting time.

BÉNÉFICES

- CHRYSO®Omega 85S allows concrete with an important workability to be obtained, while reducing the water/cement ratio.
- Enhances the workability retention of concrete particularly in hot climates.
- The dispersion properties of CHRYSO®Omega 85S allow the user to optimise the cement content when a specified mechanical strength is required.

DOMAINES D'APPLICATION

- Ready-mix concrete
- All cement types
- Reinforced concrete
- Workability retention
- High strength performance

CHARACTERISTICS

Product Nature	liquid
Color (COL)	Light brown
Lifetime	24 month
Density	1,070 ± 0,020
pH	5,00 ± 2,00

MODE D'EMPLOI

- This product must be added to the mixing water or at the end of the mixing cycle.
- The optimum dosage of this product can only be established after trial tests, taking into account the rheological properties, the strength performances and factors acting on workability.
- A 1.0% dosage of the product to the weight of cementitious is commonly used.

Dosage :

- 0.5 kg to 2.0 kg for 100 kg of cementitious materials.

PRÉCAUTIONS

- Protect from frost.
- Avoid prolonged exposure to high temperatures.

INFORMATIONS NORMATIVES ET RÉGLEMENTAIRES

- This product conforms to NF 085 certification, which technical specifications are those applied in the non harmonised part of NF EN 934-2.
- This product conforms to CE marking. The appropriate declaration can be found on our internet site.
- This product Conforms to ASTM C494 Type A, F and G and BS EN 934-2



CHRYSO® Omega 85S

High Range Water Reducing Admix

PACKAGING

- 1000 L IBC
- 200 L drum
- 20 L bucket

SÉCURITÉ

CHRYSO® Omega 85S is not considered dangerous to handle. Please refer to the material safety data sheet for additional information.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.ph

CHRYSO PHILIPPINES INC. 17 Main Ave. Severina Industrial Estate, ACSIE Comp. Km 16, West Service Rd. 1700 Paranaque City. Tél.:(+632) 823-1568 Fax:(+632) 823-6492